

Latitude Edge 11' Cable SRL-P

*See chart for part numbers, hook configurations, and product weights

FEATURES :

- Unique protective shock pack cover with mesh lining for cool-air comfort.
- Convenient harness fastener straps for added security.
- Behind-the-web bracket attaches easily.
- Durable housing for added dependability.
- 360/180° attachment point swivels for full range of motion.
- Designed for sharp leading edges with foot-level connection.
- Single leg and dual leg options available.
- Available with various hook options, see chart.
- All components are Z359.12 compliant.



Class
2
Anchor above or below dorsal D-ring

USER WEIGHT CAPACITY

ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

STANDARD COMPLIANT WITH

ANSI	Z359.14-2021
OSHA	1910.140, 1910.66

ANSI CLASS 1

Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.3 kg)
Max. arrest distance	≤ 42 in. (107 cm)
Actual arrest distance	≤ 19 in. (48 cm)
Max. free fall distance	24 in. (61 cm)
Min. required fall clearance	5 ft. 7 in. (1.7 m)
For full clearance requirements, see user instructions	

ANSI CLASS 2

Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.3 kg)
Max. arrest distance	N/A
Actual arrest distance	≤ 121 in. (307 cm)
Max. free fall distance	72 in. (152 cm)
Min. required fall clearance	17 ft. 1 in. (5.2 m)
For full clearance requirements, see user instructions	

MATERIAL SPECIFICATION

Cable	3/16" galvanized steel
Bracket	Steel, aluminum (dependent on configuration)
Housing	Nylon
Hook options	Steel, aluminum, dielectric (dependent on configuration)
Shock pack	Polyester

Latitude Edge 11' Cable SRL-P



Standards: ANSI Z359.14-2021
OSHA 1910.140 & 1910.66

Capacity: ANSI 130-310 lbs. (59-141 kg)
OSHA Up to 420 lbs. (191kg)

CONNECTOR										ATTACHMENT																									
Part Number	Single Leg (S) / Dual Leg (D)	Working Length (ft.)	Lifeline Material	Lifeline Dimensions (in.)	Housing Material	Weight (lbs.)	CONNECTOR											ATTACHMENT																	
							Li Steel Swivel Snap Hook ①	Steel Snap Hook ②	Dielectric Snap Hook ③	Steel Tie Back Hook ④	Li Steel Swivel Rebar Hook ⑤	Steel Swivel Rebar Hook ⑥	Steel Swivel Rebar Hook ⑦	ALU Swivel Rebar Hook ⑧	Steel Captive Eye Carabiner ⑨	ALU Captive Eye Carabiner ⑩	ALU Swivel Carabiner ⑪	Tip Lock Steel Carabiner ⑫	Steel Carabiner ⑬	ALU Captive Eye Carabiner ⑭	ALU Carabiner ⑮	ALU Snap Hook ⑯	ES-EX-13 ⑰	Cab Mount Bracket ⑱	Integrated BWS ⑲	Soft Loop ⑳	104 BWS ㉑	9012 BWS ㉒	9013 BWS ㉓						
SW8005-8LE	1, 2	S	8	Steel Cable	ø3/16	Nylon	5.1	X																					X						
SW8005-8LE-ALU	1, 2	S	8	Steel Cable	ø3/16	Nylon	4.6			X																			X						
SW8005-8LE-RBH	1, 2	S	8	Steel Cable	ø3/16	Nylon	5.6					X																	X						
SW8005-8LE-RBHALU	1, 2	S	8	Steel Cable	ø3/16	Nylon	5.4								X														X						
SW8005-8LE-DL	1, 2	D	8	Steel Cable	ø3/16	Nylon	9.1	X																					X						
SW8005-8LE-ALUDL	1, 2	D	8	Steel Cable	ø3/16	Nylon	8.5			X																			X						
SW8005-8LE-RBHD	1, 2	D	8	Steel Cable	ø3/16	Nylon	10.5					X																	X						
SW8005-8LE-RBHALUDL	1, 2	D	8	Steel Cable	ø3/16	Nylon	10.1								X														X						
SW8008-11LE	1, 2	S	11	Steel Cable	ø3/16	Nylon	5.1	X																					X						
SW8008-11LE-ALU	1, 2	S	11	Steel Cable	ø3/16	Nylon	4.9			X																			X						
SW8008-11LE-RBH	1, 2	S	11	Steel Cable	ø3/16	Nylon	6.1					X																	X						
SW8008-11LE-RBHALU	1, 2	S	11	Steel Cable	ø3/16	Nylon	5.7								X														X						
SW8008-11LE-DL	1, 2	D	11	Steel Cable	ø3/16	Nylon	9.2	X																					X						
SW8008-11LE-ALUDL	1, 2	D	11	Steel Cable	ø3/16	Nylon	8.8			X																			X						
SW8008-11LE-RBHD	1, 2	D	11	Steel Cable	ø3/16	Nylon	11.2					X																	X						
SW8008-11LE-RBHALUDL	1, 2	D	11	Steel Cable	ø3/16	Nylon	10.4								X														X						

